

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR									
1	Manufacturer: Kaishan Compressor USA								
	Model Number: KR	SP-300-100 VSD		Date:	08/30/20				
2	X Air-cooled	Water-cooled		Type:	Screw				
	X Lubricated	Lubricated Light Oil Free			1				
3*	Full Load Operating Pres	d Operating Pressure b		b psig					
4		ve Motor Nominal Rating		hp					
5	Drive Motor Nominal Ef	rive Motor Nominal Efficiency		percent					
6	Fan Motor Nominal Rati	n Motor Nominal Rating (if applicable)		hp					
7	Fan Motor Nominal Effi			percent					
8*	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d					
	271.3		1521	17.84					
	179.1		1049	17.07					
	130.2		730	17.84					
	105.8		578	18.30					
	67.8		335	20.24					
9*	Total Package Input Power at Zero Flow c, d		0.0 75.89	kW					
10	Isentropic Efficiency	Isentropic Efficiency			%				
11	35.00 30.00 30.00 Specific Power (kW/100 ACFN) 25.00 15.00 10.00 0	Note: Graph is only a vi- Note: Y-Axis Scale, 10 to 35,	600 800 1000 Capacity (ACFM) sual representation of the data in + 5kW/100acfm increments if neco	Section 8	1400 1600				

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org





wember

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Zero Flow Power
$\underline{\mathbf{m}}^3 / \underline{\mathbf{min}}$	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	17- 1070
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2 12/19 R3

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.