

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR										
1	1 Manufacturer: Kaishan Compressor USA									
	Model Number: KRSP-300-125 VSD			Date:	08/30/20					
2	X Air-cooled	X Air-cooled Water-cooled			Screw					
	X Lubricated Oil Free			# of Stages:	1					
3*	Full Load Operating Press	re ^b 125		psig ^b						
4	Drive Motor Nominal Rating		300	hp						
5	Drive Motor Nominal Efficiency		96.2	percent						
6	Fan Motor Nominal Ratin	an Motor Nominal Rating (if applicable) 7.5 &1.5		hp						
7	Fan Motor Nominal Effici	ency	87.5 & 91.0	percent						
	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d						
	276.3		1422	19.43						
8*	182.9		985	18.57						
	133.1		682	19.52						
	108.2		534	20.26						
	69.4		317	21.89						
9*	Total Package Input Power at Zero Flow c, d		0.0 78.52	kW						
10	Isentropic Efficiency	ropic Efficiency		%						
11	35.00 30.00 30.00 Specific Power (KWIGE) 25.00 20.00 3	Note: Graph is only a vis Note: Y-Axis Scale, 10 to 35,	600 800 1000 Capacity (ACFM) sual representation of the data in + 5kW100acfm increments if neces to 25% over maximum capacity		1400 1600					

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org





wember

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Zero Flow Power
m ³ /min	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	17- 1070
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2

12/19 R3

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.