## **COMPRESSOR DATA SHEET**



In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR										
1	Manufacturer: Kaishan Compressor USA									
	Model Number	: KRSP2-75-10	00 VSD		Date:	02/23/21				
2	X Air-cooled Water-cooled				Type:	Screw				
					# of Stages:	2				
3*	Full Load Operating Pressure b			100		psig				
4	Drive Motor Nominal Rating			75	hp					
5	Drive Motor Nominal Efficiency			96.6	percent					
6	Fan Motor Nominal Rating (if applicable)			3	hp					
7	Fan Motor Nominal Efficiency			89.3	percent					
	Input Power (kW)			Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>					
	69.3			411	16.86					
8*	47.8			288	16.60					
	34.0			206	16.50					
	28.4			164	17.32					
	20.1		- 1	103	19.51					
9*	Total Package Input Power at Zero Flow c, d		Flow c, a	0.0 78.95	kW					
10	Isentropic Effic	Isentropic Efficiency				%				
11	Note: Graph is only a visua Note: Y-Axis Scale, 10 to 35, + 5			apacity (ACFM)	n Section 8	375 400 425 450				

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: <a href="www.cagi.org">www.cagi.org</a>

NOTES:



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
  ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below: NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

	olume Flow Rate pecified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m <sup>3</sup> / min	ft <sup>3</sup> / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	17- 1070
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.